

Dutch Campers 2016 'Lely Runner' Specifications UK Model (XL model in parenthesis)

Principal Dimensions:

- Alcove Bed Size 1450 X 2000 mm
- Sofa Bed Size 800 X 2000 mm (1100 x2000mm)
- Inside Floor Length 2200mm (2500mm)
- Overall Width 2070 mm
- Headroom 1950mm std 2000 mm on request
- Weight Ca. 655 kg (705kg) with series specification

Specifications:

- Lightweight expedition grade vacuum bonded body. Exceptionally strong & durable. Totally impermeable to water no leaks, no timber frame to rot.
- Woven Roving GRP inner and outer wall panels with tough gelcoat finish. Outer walls additionally finished in solid RAL colour of your choice.
- Inner walls finished with special soft touch 'tactile' lining.
- 30 mm Styrofoam insulation with no cold bridges virtually eliminating condensation
- 4 x flush-fit double glazed windows. Robust alloy frame with special 'zero cold' bridge construction.
- All windows fitted with Blackout blinds and Fly Screens
- 2 x Heki Skylights with Blackout and Fly Screens
- Stainless jacking and mounting system
- All external bolts/screws/fasteners in stainless steel
- Hella LED road lighting and 'porch' light
- Aerodynamic alcove
- Slatted mattress base with 12 cm thick cold foam luxury mattress (breathable system)
- Hard wearing and attractive, marine grade upholstery with choice of colours
- CAN 2 burner gas hob and sink with individual glass covers
- 65 litre Isotherm compressor fridge/freezer³
- Tough and attractive vinyl flooring with choice of colours and finishes
- · Attractive and robust furniture in 15 mm special lightweight ply with choice of finish and trim
- Adjustable table (730 x 730mm)
- 12 cm foam seat cushions and contoured back cushions
- Copious cupboards clever use of every space provides ample, practical storage
- Touch sensitive, dimmable led lighting throughout
- Trumatic S 2200 gas heating
- Fully integrated marine grade 12 volt system with comprehensive systems display panel
- Fully integrated 220 volt system with CEE protection
- 15 amp Victron battery charger
- 1 each 12 volt aux, 12 volt DIN and 5 volt USB outlets
- 3 x UK 220 volt outlets
- True deep cycle battery 110 a/h
- Washroom size 870 x 820 mm (900 x 820mm) including Dometic CTS 4110 flushing toilet, washbasin, cupboards and mirror
- Fiamma Crystal Vent with fly screen in washroom: size 280 x 280 mm
- External gas locker for 2 x 6 kilo gas cylinders
- Multigas (universal) propane/butane regulator

- Fresh water tank 48 litre with external city/gravity fill connection
- Fiamma iSensor constant pressure water pump
- 30 litre grey water tank
- SOPO gas/carbon monoxide/smoke detector
- CE certified fire extinguisher
- Mounting kit¹ (for trucks equipped with towbar)
- 2 year manufacturers warranty

Regular Options:

- Hot water boiler Truma B10 KBS3 10 litre (gas)
- Oven/Grill Dometic type Smev FO211GT
- Microwave (shore-power only or requires inverter²)
- Microwave/Grill (shore-power only or requires inverter²)
- Inverter² (required for microwave options when no shore-power available)
- 85 litre fridge/freezer in place of 65 litre
- 90 litre 3 way (absorption) fridge³ Note: absorption fridges are effective only while stationary (gas or 220v operation). They do not provide effective cooling while travelling (12v operation)
- Shower in washroom (XL model only)
- · Outdoor shower
- Cupboards in Alcove left or right of bed
- North/South bed arrangement for Alcove bed including additional cupboards each side
- Additional 220 volt/12 volt sockets
- Double usb socket with high output (2.1amp) and standard outlets
- Outdoor gas connection
- 65 litre fresh water tank (in place of 48 litre standard)
- Roof rack 'Omnistor' (must be specified at time of order)
- · Ladder 'Omnistor'
- Bicycle Rack In Stainless Steel (includes additional locking for rear door)
- Side Awning Fiamma or Omnistor 2,5 meter (XL 3.0 meter)
- Rear 'Porch' Awning (Fiamma) 1.8 meter
- Heki Midi in place of standard Heki
- Heki 1 Maxi in place of standard Heki
- Solar panel 40 watt flat mounted solar panel
- Solar panel 100 watt flat mounted solar panel with MPPT controller
- Additional solar panel 100 watt
- Additional solar panel 90 watt flat
- AGM deep cycle battery 140 a/h
- 25 Amp Battery Charger (in place of 16amp)
- Lithium-ion battery 40 a/h
- 'Teleco' satellite with led TV (12 volt)
- Folding worktop/ shelf next to sink
- · Gas regulator Truma 'Duo Control'
- 6 kilo Gaslow 'R67 certified' refillable gas bottle and external filling point. Duo system with Camping Gaz 907 reserve. Complete with adapters for all European destinations.
- As above with dual 6 kilo Gaslow refillable gas bottles and automatic change over.
- SOG toilet ventilation
- Air conditioning Dometic Freshjet 1100 (shore-power only or requires inverter²)
- Heated and Insulated Grey Water Tank
- Lely or Glostep scissor step 3 steps
- Lely or Glostep scissor step 4 steps
- Rear view camera with in cab displayBattery monitor Victron/Merlin
- 'Battery to Battery' charger (highly recommended in all cases, obligatory for all Euro 5/6 base vehicles if efficient battery charging from base vehicle is required)
- Electrical connection kit for truck¹ (if tow bar not fitted)
- Carbon Fibre body shell outer skin (in place of GRP)
- External finish in Metallic or non RAL paint colour.
- Turbo Liner® MPL11 to camper floor and lower sections.
- Turbo Liner® MPL11 to truck bed and sides.
- Air assisted rear suspension for Japanese 4x4/Ford Ranger (highly recommended for all applications especially Double Cab base vehicles).